What is claimed is:

1. An image-processing method comprising the steps of:

reconstructing an image which has a resolution differing from a reference-resolution, based on an image signal subjected to a multiple-resolution transformation process; and

calculating an image-processing parameter, based on a reference-processing parameter employed in performing a predetermined image-processing process on a reference-resolution image having said reference resolution, said image-processing parameter being employed in performing said predetermined image-processing process on the reconstructed image and causing the image characteristics of said reconstructed image subjected to said predetermined image-processing process to be substantially the same as the image characteristics of said reference-resolution image subjected to said predetermined image-processing process.

2. The image-processing method as set forth in claim 1, wherein said image signal is subjected to said multiple-resolution transformation process so that the resolution of each image is 2^k (where k is an integer) times that of said reference-resolution, and the image-size of each image is 2^{2k} times the image-size of said reference-resolution image; and

said reconstructed image is an image having a resolution which does not fall within the 2^k times range of said reference-resolution.

3. The image-processing method as set forth in claim 1, wherein said reconstructed image subjected to said predetermined image-processing process is further converted to an image having a desired image-size.

4. The image-processing method as set forth in claim 2, wherein said reconstructed image subjected to said predetermined image-processing process is further converted to an image having a desired image-size.

5. The image-processing method as set forth in claim 2, wherein said reconstructing is performed so that the image-size of said reconstructed image is 2^{2k} times the image-size of said reference-resolution image, close to the image-size of an image which is to be reproduced and output as a visible image; and

an image subjected to said predetermined image-processing process is further subjected to a zoom process so that it becomes equal in size to the image-size of said output image.

6. The image-processing method as set forth in claim 1, wherein said reference-processing parameter is stored in correlation with said image signal.

7. The image-processing method as set forth in claim 2, wherein said reference-processing parameter is stored in correlation with said image signal.

8. The image-processing method as set forth in claim 3, wherein said reference-processing parameter is stored in

51

correlation with said image signal.

9. The image-processing method as set forth in claim 5, wherein said reference-processing parameter is stored in correlation with said image signal.

10. The image-processing method as set forth in claim 1, wherein said image-processing parameter is calculated based on the characteristic of said multiple-resolution transformation process.

11. The image-processing method as set forth in claim 2, wherein said image-processing parameter is calculated based on the characteristic of said multiple-resolution transformation process.

12. The image-processing method as set forth in claim 3, wherein said image-processing parameter is calculated based on the characteristic of said multiple-resolution transformation process.

13. The image-processing method as set forth in claim 5, wherein said image-processing parameter is calculated based on the characteristic of said multiple-resolution transformation process.

14. The image-processing method as set forth in claim 6, wherein said image-processing parameter is calculated based on the characteristic of said multiple-resolution transformation process.

15. An image-processing system comprising:

reconstruction means for reconstructing an image

which has a resolution differing from the reference-resolution, based on an image signal subjected to a multiple-resolution transformation process;

image-processing means for performing a predetermined image-processing process on the reconstructed image; and

parameter-setting means for deriving an image-processing parameter, based on a reference-processing parameter employed in performing a predetermined image-processing process on a reference-resolution image having said reference-resolution, and setting the derived image-processing parameter to said image-processing means, said image-processing parameter being employed in performing said predetermined image-processing process on said reconstructed image and causing the image characteristics of said reconstructed image subjected to said predetermined image-processing process to be substantially the same as the image characteristics of said reference-resolution image subjected to said predetermined image-processing process, approximately the same.

16. The image-processing system as set forth in claim 15, wherein said image signal is subjected to said multiple-resolution transformation process so that the resolution of each image is 2^k (where k is an integer) times that of said reference-resolution and an image-size of each image is 2^{2k} times that of the image-size of said reference-resolution image; and

said reconstruction means obtains said reconstructed image having a resolution not falling within the 2^k times range of said reference-resolution.

17. The image-processing system as set forth in claim 15, further comprising zoom-processing means for further converting said reconstructed image subjected to said predetermined image-processing process, to an image having a desired image-size.

18. The image-processing system as set forth in claim 16, further comprising zoom-processing means for further converting said reconstructed image subjected to said predetermined image-processing process, to an image having a desired image-size.

19. The image-processing system as set forth in claim 16, wherein said reconstruction means reconstructs an image so that the image-size of said image is 2^{2k} times the image-size of said reference-resolution image, close to the image-size of an image which is reproduced and output as a visible image; and

zoom-processing means is further provided for performing a zoom process on an image subjected to said predetermined image-processing, so that it becomes equal in size to the image-size of said output image.

20. The image-processing system as set forth in claim 15, wherein said parameter-setting means derives said image-processing parameter, based on the characteristic of said multiple-resolution transformation process.

54

21. The image-processing system as set forth in claim 16, wherein said parameter-setting means derives said image-processing parameter, based on the characteristic of said multiple-resolution transformation process.

22. The image-processing system as set forth in claim 17, wherein said parameter-setting means derives said image-processing parameter, based on the characteristic of said multiple-resolution transformation process.

23. The image-processing system as set forth in claim 19, wherein said parameter-setting means derives said image-processing parameter, based on the characteristic of said multiple-resolution transformation process.

24. A computer readable storage medium recording a program to be executed by a computer, said program comprising:

a procedure for reconstructing an image having a resolution differing from the reference-resolution, based on an image signal subjected to a multiple-resolution transformation process;

a procedure for calculating an image-processing parameter, based on a reference-processing parameter employed in performing a predetermined image-processing process on a reference-resolution image having said reference-resolution, said image-processing parameter being employed in performing said predetermined image-processing on said reconstructed image and causing the image characteristics of said reconstructed image subjected to said predetermined image-processing to be

55

substantially the same as the image characteristics of said

reference-resolution image subjected to said predetermined

image-processing; and

a procedure for performing said predetermined

image-processing process on said reconstructed image by use of

said image-processing parameter.

25. The storage medium as set forth in claim 24,

wherein said image signal is subjected to said multiple-

resolution transformation process so that the resolution of each

image is 2^k (where k is an integer) times that of said

reference-resolution, and the image-size of each image is 2^{2k}

times that of the image-size of said reference-resolution image;

and

said reconstructing procedure is a procedure for

obtaining said reconstructed image having a resolution not

falling within the 2^k times range of said reference-resolution.

26. The storage medium as set forth in claim 24

further comprising a procedure of further converting said

reconstructed image subjected to said predetermined image-

processing process, to an image having a desired image-size.

27. The storage medium as set forth in claim 25

further comprising a procedure of further converting said

reconstructed image subjected to said predetermined image-

processing, to an image having a desired image-size.

28. The storage medium as set forth in claim 24,

wherein said reconstructing means is a procedure of

56

reconstructing an image so that the image-size of said image is 2^{2k} times the image-size of said reference-resolution image, close to the image-size of an image to be reproduced and output as a visible image; and

a zooming procedure is further provided for performing a zoom process on an image subjected to said predetermined image-processing, so that it becomes equal in size to the image-size of said output image.

29. The storage medium as set forth in claim 24, wherein said parameter calculating procedure is a procedure of calculating said image-processing parameter, based on the characteristic of said multiple-resolution transformation process.

30. The storage medium as set forth in claim 25, wherein said parameter calculating procedure is a procedure of calculating said image-processing parameter, based on the characteristic of said multiple-resolution transformation process.

31. The storage medium as set forth in claim 26, wherein said parameter calculating procedure is a procedure of calculating said image-processing parameter, based on the characteristic of said multiple-resolution transformation process.

32. The storage medium as set forth in claim 28, wherein said parameter calculating procedure is a procedure of calculating said image-processing parameter, based on the

characteristic of said multiple-resolution transformation

process.